

## Claims

1. A method of operating a chemical-vapor-deposition system including a gas-dispersion fixture and having a normal deposition temperature for forming material layers of a predetermined composition, the method comprising:  
forming a first material layer of the predetermined composition on the gas-dispersion fixture at a first nominal or average temperature which is different than the normal deposition temperature; and  
using the gas-dispersion fixture to form a second material layer of the predetermined material layer on a substrate at the normal deposition temperature.
2. The method of claim 1, wherein the first nominal or average temperature differs by more than five percent from the normal deposition temperature.
3. The method of claim 1, wherein the first nominal or average temperature differs by more than 15 percent from the normal deposition temperature.
4. The method of claim 1, wherein the first nominal or average temperature differs by more than 20 percent from the normal deposition temperature.
5. The method of claim 1, wherein the first nominal or average temperature differs by more than 50 percent from the normal deposition temperature.
6. The method of claim 1, wherein the first nominal or average temperature is greater than the normal deposition temperature.
7. A method of operating a chemical-vapor-deposition system including a gas-dispersion fixture and having a normal deposition temperature for forming material layers of a predetermined composition, the method comprising:

forming a first material layer of the predetermined composition on the gas-dispersion fixture at a first nominal or average temperature which is substantially greater than the normal deposition temperature; and using the gas-dispersion fixture to form a second material layer of the predetermined material layer on a substrate at the normal deposition temperature, after forming the first material layer.

8. A method of conditioning a gas-dispersion fixture in a chemical-vapor-deposition system having a normal deposition temperature for forming material layers of a predetermined composition, the method comprising:

heating at least a portion of the gas-dispersion fixture to a temperature greater than the normal deposition temperature; and forming a material layer of the predetermined composition on at least the portion of the gas-dispersion fixture.

9. The method of claim 8, wherein the gas-dispersion fixture comprises a showerhead.

10. The method of claim 8, wherein heating occurs before forming the material layer.

11. The method of claim 8:

wherein the chemical-vapor-deposition system includes a heated substrate holder, with the heated substrate holder having a normal position relative the gas-dispersion fixture to form material layers of the predetermined composition; and

wherein heating at least a portion of the gas-dispersion fixture to a temperature greater than the normal deposition temperature comprises moving the fixture closer to the heated substrate holder than its normal position.

12. The method of claim 11, wherein moving the fixture closer to the heated substrate holder than its normal position comprises moving the fixture within 300 mils of the substrate holder.
13. The method of claim 8, further comprising introducing a plasma power of over 400 watts near the gas-dispersion fixture.
14. The method of claim 8, wherein forming the material layer of the predetermined composition on at least the portion of the gas-dispersion fixture, comprises passing one or more gases through the gas-dispersion fixture.
15. The method of claim 8, wherein the material layer consist essentially of titanium, aluminum, chlorine, and nitrogen atoms.
16. A method of forming a layer in an integrated circuit, comprising:  
conditioning a gas-dispersion fixture in a chemical-vapor-deposition system  
having a normal deposition temperature for forming material layers  
of a predetermined composition, wherein conditioning comprises:  
heating at least a portion of the gas-dispersion fixture to a  
temperature greater than the normal deposition temperature  
by at least ten percent; and  
forming a material layer of the predetermined composition on at least  
the portion of the gas-dispersion fixture; and  
using the gas-dispersion fixture to form the layer in the integrated memory  
circuit.
17. The method of claim 16, wherein the material layer consist essentially of titanium, aluminum, chlorine, and nitrogen atoms.
18. The method of claim 16, wherein the material layer comprises titanium.

19. A method of forming a layer on a surface of a gas-dispersion fixture in a chemical-vapor-deposition system having a normal deposition temperature for forming material layers of a predetermined composition, the method comprising:

heating at least a portion of the surface of the gas-dispersion fixture to a temperature greater than the normal deposition temperature by at least ten percent; introducing one or more gases around the heated surface of the gas-dispersion fixture; and electrically exciting the one or more gases to create a plasma.

20. A method of conditioning a gas-dispersion fixture in a chemical-vapor-deposition system including a heated substrate holder, with the system having a normal deposition temperature for forming material layers of a predetermined composition and the heated substrate holder having a first separation from the gas-dispersion fixture to form material layers of the predetermined composition, the method comprising:

establishing a second separation between the gas-dispersion fixture and the heated substrate holder, with the second separation being less than the first separation; and forming a material layer of the predetermined composition on at least the portion of the gas-dispersion fixture while the second separation is established.

21. The method of claim 20, wherein the material layer consist essentially of titanium, aluminum, chlorine, and nitrogen atoms.

22. The method of claim 20, wherein the material layer comprises titanium.

23. A method of conditioning a gas-dispersion fixture in a chemical-vapor-deposition system including a heated substrate holder, with the system having a normal deposition temperature for forming material layers of a predetermined

composition and the heated substrate holder having a first separation from the gas-dispersion fixture to form material layers of the predetermined composition, the method comprising:

establishing a second separation between the gas-dispersion fixture and the heated substrate holder, with the second separation being less than the first separation;

operating the heated substrate holder to heat at least a portion of the gas-dispersion fixture to a temperature greater than the normal deposition temperature; and

forming a material layer of the predetermined composition on at least the portion of the gas-dispersion fixture while the second separation is established and while the portion of the gas-dispersion fixture has a temperature greater than the normal deposition temperature.

24. The method of claim 23, wherein the material layer consist essentially of titanium, aluminum, chlorine, and nitrogen atoms.

25. The method of claim 23, wherein the material layer comprises titanium.

26. A method of conditioning a gas-dispersion fixture in a chemical-vapor-deposition system including a heated substrate holder, with the system having a normal deposition temperature for forming material layers of a predetermined composition and the heated substrate holder having a first separation from the gas-dispersion fixture to form material layers of the predetermined composition, the method comprising:

establishing a second separation between the gas-dispersion fixture and the heated substrate holder, with the second separation being less than the first separation;

operating the heated substrate holder to heat at least a portion of the gas-dispersion fixture to a temperature greater than the normal deposition temperature;

forming a material layer of the predetermined composition on at least the portion of the gas-dispersion fixture while the second separation is established and while the portion of the gas-dispersion fixture has a temperature greater than the normal deposition temperature, wherein forming the material layer comprises:

introducing one or more gases around the heated portion of the gas-dispersion fixture; and  
electrically exciting the one or more gases.

27. The method of claim 26, wherein operating the second separation occurs prior to operating the heated substrate holder to heat the portion of the gas-dispersion fixture and wherein forming the material layer occurs after operating the heated substrate holder.

28. The method of claim 26, wherein the material layer consist essentially of titanium, aluminum, chlorine, and nitrogen atoms.

29. The method of claim 26, wherein the material layer comprises titanium.

30. A method of conditioning a showerhead in a chemical-vapor-deposition system including a heated substrate holder, with the system having a normal deposition temperature for forming material layers of a predetermined composition and the heated substrate holder having a first separation from the showerhead to form material layers of the predetermined composition, the method comprising:

establishing a second separation between the showerhead and the heated substrate holder, with the second separation being less than the first separation;

operating the heated substrate holder to heat at least a portion of the showerhead to a temperature greater than the normal deposition temperature;  
forming a material layer of the predetermined composition on at least the portion of the showerhead while the second separation is established and while the portion of the showerhead has a temperature greater than the normal deposition temperature, wherein forming the material layer comprises:  
introducing one or more gases around the heated portion of the showerhead; and  
electrically exciting the one or more gases to create a plasma.

31. The method of claim 30, wherein operating the second separation occurs prior to operating the heated substrate holder to heat the portion of the showerhead and wherein forming the material layer occurs after operating the heated substrate holder.

32. The method of claim 30, wherein heating occurs before forming the material layer.

33. The method of claim 30, wherein the second separation is less than or equal to 300 mils.

34. The method of claim 30, wherein the plasma has a power greater than about 400 watts.

35. The method of claim 30, wherein forming the material layer of the predetermined composition on at least the portion of the gas-dispersion fixture, comprises passing one or more gases through the gas-dispersion fixture.

36. The method of claim 30, wherein the material layer consist essentially of titanium, aluminum, chlorine, and nitrogen atoms.

37. A method of operating a chemical-vapor-deposition system including a gas-dispersion fixture and a heated substrate holder, with the system having a normal deposition temperature for forming material layers of a predetermined composition and the heated substrate holder having a first separation from the gas-dispersion fixture to form material layers of the predetermined composition, the method comprising:

establishing a second separation between the gas-dispersion fixture and the heated substrate holder, with the second separation being less than the first separation;

operating the heated substrate holder to heat at least a portion of the gas-dispersion fixture to a temperature greater than the normal deposition temperature;

forming a material layer of the predetermined composition on at least the portion of the gas-dispersion fixture while the second separation is established and while the portion of the gas-dispersion fixture has a temperature greater than the normal deposition temperature, wherein forming the material layer comprises:

introducing one or more gases around the heated portion of the gas-dispersion fixture; and

electrically exciting the one or more gases to create a plasma;

re-establishing the first separation between the gas-dispersion fixture and the heated substrate holder;

placing a substrate on the heated substrate holder;

heating the substrate to the normal deposition temperature; and

forming a material layer of the predetermined composition on at least a portion of the substrate at the normal deposition temperature.



38. A method of operating a chemical-vapor-deposition system including a gas-dispersion fixture and a heated substrate holder, with the system having a normal deposition temperature for forming material layers of a predetermined composition and the heated substrate holder having a first separation from the gas-dispersion fixture to form material layers of the predetermined composition, the method comprising:

establishing a second separation between the gas-dispersion fixture and the heated substrate holder, with the second separation being less than the first separation;

operating the heated substrate holder to heat at least a portion of the gas-dispersion fixture to a temperature greater than the normal deposition temperature;

forming a material layer of the predetermined composition on at least the portion of the gas-dispersion fixture while the second separation is established and while the portion of the gas-dispersion fixture has a temperature greater than the normal deposition temperature by at least 20 percent, wherein forming the material layer comprises:

introducing one or more gases around the heated portion of the gas-dispersion fixture; and

electrically exciting the one or more gases to create a plasma;

re-establishing the first separation between the gas-dispersion fixture and the heated substrate holder;

placing a substrate on the heated substrate holder;

heating the substrate to the normal deposition temperature; and

forming a material layer of the predetermined composition on at least a portion of the substrate at the normal deposition temperature.

39. In a chemical-vapor-deposition system including a susceptor and a gas-dispersion fixture and having a normal deposition temperature and a normal separation between the susceptor and the gas-dispersion fixture for forming material

22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100																					
101	102	103	104	105	106	107	108	109	110	111	112	113	114	115	116	117	118	119	120	121	122	123	124	125	126	127	128	129	130	131	132	133	134	135	136	137	138	139	140	141	142	143	144	145	146	147	148	149	150	151	152	153	154	155	156	157	158	159	160	161	162	163	164	165	166	167	168	169	170	171	172	173	174	175	176	177	178	179	180	181	182	183	184	185	186	187	188	189	190	191	192	193	194	195	196	197	198	199	200

22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100																					
101	102	103	104	105	106	107	108	109	110	111	112	113	114	115	116	117	118	119	120	121	122	123	124	125	126	127	128	129	130	131	132	133	134	135	136	137	138	139	140	141	142	143	144	145	146	147	148	149	150	151	152	153	154	155	156	157	158	159	160	161	162	163	164	165	166	167	168	169	170	171	172	173	174	175	176	177	178	179	180	181	182	183	184	185	186	187	188	189	190	191	192	193	194	195	196	197	198	199	200